



JWD1-16



JWD1-35

端子厚度 12.2

刚性导线 柔性导线 (mm ²)		I (A)	U (V)
IEC 60947-7-1	2.5-25 4-16	101	800
型 号	订 货 号	包 装 数	
JWD1-16	5 574 113	25	
JWD1-16 BU	5 574 114	25	
16G	8 050 105	50	
16G BU	8 050 106	50	
ZL 12/10	5 585 160	10	
LJ 12/2	5 583 106	10	
BL 12/10	5 582 160	10	
GP	8 751 101	100	
1.5-16 GF	8 750 101	10	
16 JS	8 867 106	10	
ZP10(订货数据见45页)			
12.2/42.5/1.5			
54/61.5/59			
101/25			
16/16			
8/3			
III/I			
1.5-16/1.5-16			
1.5-6/1.5-4			
1.5-6			
0.75-10			
11			
M4			
1.5-1.8			
PA			
V0			
600/85/22-4			



端子厚度 15.2

刚性导线 (mm²)		柔性导线	I (A)	U (V)
IEC 60947-7-1	0.75-50	0.75-35	150	1000
型 号	订货号		包装数	
JWD1-35	5 574 117		25	
JWD1-35 BU	5 574 118		25	
ZL 15/10	5 585 170		10	
LJ 15/2	5 583 107		10	
TL15-6	5 586 102		10	
BL 15/2	5 582 162		10	
BL 15/3	5 582 163		10	
BL 15/10	5 582 170		10	
HL 15/2 只带短搭接钩片	5 581 105		1	
GP	8 751 101		100	
35 JS	8 867 107		10	
ZP10(订货数据见45页)				
15.2/50/- 62/69.5/67				
150/50 35/35 8/3 III/I				
0.75-35/0.75-35				
0.75-16/0.75-10 0.75-10 0.75-6				
16				
M6				
3.2-3.7				
PA				
V0				
1000/150/18-10				

