


RCCN 日成BGF型金属快速软管防水接头 Water Conduit Connector



螺母规格:公制螺母(Metric).

产品材质:A.C.F部位均采用锌合金镀镍制成.B.D采用硅橡胶制成。

产品认证:欧洲CE,ROHS.

防护等级:在规定的卡口范围内,并使用O形密封圈旋紧迫紧头,达到IP68.

产品特性:配套锁紧式电缆接头,防电线松动,内锁扣和本体特殊设计,装卸只需拨插无需工具,大大缩短了安装时间. 夹紧电缆范围大,抗拉力特强,可防水、防尘、抗盐、耐酸碱、酒精、油、脂及一般溶剂.

Thread:Metric

Material:A.C.F are made of zinc metal plated with nickel.B.D are made of rubber

Certificates:CE,ROHS.

Protect rate:in bayonet scope,usd with O ring,screw down lock nut,can be up to IP68

Product characteristics:Special design of part D and E,used with part F, can save your time,large spread of cable sealing,good re-tensile,waterproof,ashproof,re-salty, withstand impregnant like acid,alkali,alcohol,oil,grease

单位/Unit:mm

型号 Item No.	螺牙规格 Thread	最大电缆 Cable Range Ø	对应日成软管型号 Suit to RCCN conduit item no BG	对应日成软管型号 Suit to RCCN conduit item no BG	螺纹外径 Thread O.D. D1	机板口径 Panel Mounting Hole	螺纹长度 Thread Length L1	包装 Std.Pkg. pcs
公制螺牙/Metric thread BGF-M								
* BGF-M12(BG07)	M12×1.5	5	BG-07	10.0	12	12-12.3	6	10PCS
BGF-M12(BG10)	M12×1.5	5	BG-10	13.0	12	12-12.3	6	
BGF-M16(BG07)	M16×1.5	8	BG-07	10.0	16	16-16.3	7	
* BGF-M16(BG10)	M16×1.5	8	BG-10	13.0	16	16-16.3	7	
BGF-M18(BG10)	M18×1.5	8	BG-10	13.0	18	18-18.3	8	
* BGF-M18(BG12)	M18×1.5	10	BG-12	15.8	18	18-18.3	8	
BGF-M18(BG15)	M18×1.5	13	BG-15	18.5	18	18-18.3	8	
BGF-M20(BG10)	M20×1.5	8	BG-10	13.0	20	20-20.3	8	
* BGF-M20(BG12)	M20×1.5	10	BG-12	15.8	20	20-20.3	8	
* BGF-M20(BG15)	M20×1.5	13	BG-15	18.5	20	20-20.3	8	
* BGF-M20(BG17)	M20×1.5	15	BG-17	21.2	20	20-20.3	8	10PCS
BGF-M22(BG17)	M22×1.5	15	BG-17	21.2	22	22-22.3	9	
BGF-M24(BG17)	M24×1.5	15	BG-17	21.2	24	24-24.3	10	
BGF-M25(BG17)	M25×1.5	15	BG-17	21.2	25	25-25.4	10	
* BGF-M25(BG23)	M25×1.5	21	BG-23	28.5	25	25-25.4	10	
BGF-M27(BG23)	M27×1.5	21	BG-23	28.5	27	27-27.4	11	
BGF-M30(BG23)	M30×1.5	21	BG-23	28.5	30	30-30.4	11	
* BGF-M32(BG23)	M32×1.5	21	BG-23	28.5	32	32-32.4	11	
BGF-M32(BG29)	M32×1.5	25	BG-29	34.5	32	32-32.4	11	
BGF-M33(BG29)	M33×1.5	25	BG-29	34.5	33	33-33.4	11	
BGF-M36(BG29)	M36×1.5	25	BG-29	34.5	36	36-36.4	11	
* BGF-M40(BG29)	M40×1.5	25	BG-29	34.5	40	40-40.4	12	
BGF-M40(BG36)	M40×1.5	33	BG-36	42.5	40	40-40.4	12	
BGF-M48(BG36)	M48×2.0	33	BG-36	42.5	48	48-48.4	12	
* BGF-M50(BG36)	M50×1.5	33	BG-36	42.5	50	50-50.4	13	
BGF-M50(BG48)	M50×1.5	45	BG-48	54.5	50	50-50.4	13	
BGF-M56(BG48)	M56×2.0	45	BG-48	42.5	56	56-56.4	13	
* BGF-M63(BG48)	M63×1.5	45	BG-48	54.5	63	63-63.4	14	

另可加工特殊型号 例:BGF-M20(BG-10) Special length can be produced, such as: BGF-M20(BG-10)