



材质:UL合格之NYLON66,防火等级94V-2,不易老化.

用途:PC板及机板之固定,取代螺丝,不需工具即可完成装配.

特点:容易固定.


用法:先将机板及被固定板钻孔,再将本产品塞入,即可使两板相线合.

板厚:以H长度小5mm为准.

开孔:建议表格孔径负公差0.2-1mm开孔.

Material: NYLON66 UL approved, fireproof 94V-2

Good quality, easy to install



单位/Unit:mm

型号 Item No.	头部 Head W	孔径 Hole dia. W1	长度 Length H	包装 Packing pcs
SR5-925	23	5.5	15.0	100pcs
SR6-158	19.6	6.0	8.1	100pcs
SR6-135	15.1	6.0	10.5	100pcs
SR6-148	14.6	6.0	10.6	100pcs
SR6-142	17.9	6.0	10.2	100pcs
SR6-510	12.7	6.8	30.5	100pcs
SR6-91	15.2	6.0	13.8	100pcs
SR6-556	18.0	6.0	12	100pcs
SR6-613	17.4	6.3	12.7	100pcs
SR6-508	15.5	6.3	22.8	100pcs
SR7-44	15.2	7.0	12.6	100pcs
SR7-92	20.2	7.0	9.0	100pcs
SR7-395	17	7.0	10.0	100pcs
SR7-72	15.4	7.0	13.4	100pcs
SR7-273	17.0	7.0	16.0	100pcs
SR7-164	22.0	7.0	9.0	100pcs
SR7-175	14.0	7.0	11.0	100pcs
SR7-325	17.0	7.0	13.0	100pcs
SR8-128	15.2	8.0	8.9	100pcs
SR8-81	20.5	8.0	20.7	100pcs
SR8-277	18.0	8.0	9.0	100pcs
SR8-80	20.0	8.0	26.0	100pcs
SR8-45	20.6	8.0	9.5	100pcs
SR8-578	18.0	8.0	12.0	100pcs
SR8-221	20	8.5	13.5	100pcs
SR9-854	18	9	19	100pcs
SR10-136	30.0	10.0	18.0	100pcs
SR10-852	18.0	10.0	19.0	100pcs
SR10-554	30	10.0	20	100pcs
SR10-18	20.4	10.0	25.1	100pcs
SR10-570	20	10.0	15	100pcs
SR11-70	22	11	13.4	100pcs

