


RCCN 日成SR型闭口旋转尼龙铆钉 Push Snap Rivets



材质:UL合格之NYLON66,防火等级94V-2,不易老化.
用途:PC板及机板之固定,取代螺丝,不需工具即可完成装配.
特点:容易固定.
用法:先将机板及被固定板钻孔,再将本产品塞入,即可使两板相线合.
板厚:以H长度小5mm为准.
开孔:建议表格孔径负公差0.2-1mm开孔.

Material : NYLON66 UL approved, fireproof 94V-2
Good quality, easy to install

单位/Unit:mm

型号 Item No.	头部 Head W	孔径 Hole dia. W1	长度 Length H	包装 Packing pcs
SR5-506	10.9	5.8	17.5	100pcs
SR6-614	17.6	6.3	19.0	100pcs
SR6-169	18	6.0	10.0	100pcs
SR6-509	25.4	6.3	17.5	100pcs
SR6-507	17.8	6.3	17.5	100pcs
SR6-334	12.0	6.0	17.0	100pcs
SR6-46	17.5	6.3	22.4	100pcs
SR6-681	25.4	6.3	25.4	100pcs
SR6-181	13.7	6.0	16.5	100pcs
SR6-240	13	6.0	20.0	100pcs
SR6-253	11	6.0	4.0	100pcs
SR6-956	18.4	6.5	25.0	100pcs
SR7-395	17	7.0	10.0	100pcs
SR7-321	22.2	7.2	20.7	100pcs
SR7-512	14.8	7.9	20.3	100pcs
SR8-573	20	8.0	20	100pcs
SR8-109	19.2	8.0	19.2	100pcs
SR8-339	16	8.0	21.0	100pcs
SR8-338	20	8.0	22.0	100pcs
SR8-341	18	8.0	18.0	100pcs
SR8-122	18.1	8.0	21.6	100pcs
SR9-111	15	9.0	26.8	100pcs
SR9-110	18.1	9.0	24.7	100pcs
SR9-666	20	9.0	26.0	100pcs
SR10-513	21.6	10.4	25.4	100pcs
SR10-116	20	10.0	23.3	100pcs
SR10-115	20	10.0	28.3	100pcs
SR12-544	21	12.0	25	100pcs
SR8-248	11	8.0	10.0	100pcs
SR8-118	19.6	8.0	14.4	100pcs
SR8-88	20.2	8.0	8.7	100pcs
SR8-107	13.6	8.0	9.1	100pcs
SR8-566	18	8.0	14.0	100pcs
SR8-541	20	8.0	14.0	100pcs
SR8-633	18	8.0	16.0	100pcs
SR8-649	18	8.0	15.0	100pcs
SR8-121	17.7	8.0	21.0	100pcs
SR8-351	18	8.0	12.5	100pcs
SR9-145	15	9.0	11.8	100pcs
SR9-680	18	9.0	12.0	100pcs
SR9-641	18	9.0	15.0	100pcs
SR9-611	18	9.0	28.0	100pcs
SR9-354	20	9.7	20	100pcs
SR9-686	18	9.0	22.0	100pcs
SR10-634	20	10	13	100pcs
SR10-89	18	10	15	100pcs
SR10-141	19	10	21.2	100pcs
SR12-149	25.4	12.7	22.7	100pcs