


RCCN 日成SR长型捶式尼龙铆钉 Push Snap Rivet



线槽或导轨专用铆钉



单位/Unit:mm

型号 Item No.		适用板厚 Panel Thick	适用孔径 Hole Dia	A	L	T	附图编号 Fig.No.	包装 Packing
白色/White	黑色/Black							
SR-0510W	SR-0510B	3.0-4.0	5.0	4.0	9.0	2.0	C	1000pcs
SR-0610W	SR-0610B	3.0-4.0	6.5	4.0	9.0	2.5	C	1000pcs
SR-0616W	SR-0616B	6.0-10.0	6.5	4.0	16.0	2.0	B	1000pcs
-	SR-0614B	5.0-9.0	6.5	3.5	14.5	2.5	A	1000pcs

材质:UL合格NYLON66 防火等级: 94V-2

用法:一体式设计,将铆钉打入即可固定线槽


特点:取代传统螺丝固定,缩短安装时间,绝缘佳.

型号说明: SR0610,SR0616,SR0614为原SR0612细分出来型号

SR-0510为原SRP-5A, SR-0616为原SRP-9A

Material : NYLON66 UL approved,fireproof 94V-2

Good quality,easy to install,good insulation



RCCN 日成SRS短型捶式尼龙铆钉 Short Push Snap Rivet



材 质:UL合格之NYLON 66(本色),

防火等级:94V-2,不易老化,绝缘度高

用途:本品适合头部不突出环境使用。

Material : NYLON66 UL approved,

Fireproof :94V-2

Good quality,easy to install



单位/Unit:mm

型号 Item No.	适用孔径 Hole Dia	适用板厚 Panel Thick	A	B	C	D	E	附图编号 Fig.No.
SRS3045	3.1	2.0-3.0	8.5	2.0	4.5	3.0	5.8	No.1
SRS3055	3.1	3.0-4.0	8.5	2.0	5.5	3.0	5.8	
SRS4050	4.1	2.5-3.5	8.0	2.2	5.0	4.0	8.0	
SRS4060	4.1	3.5-4.5	8.0	2.2	6.0	4.0	8.0	
SRS4070	4.1	4.5-5.5	8.0	2.2	7.0	4.0	11.2	No.2
SRS4080	4.1	5.5-6.5	8.0	2.2	8.0	4.0	11.2	
SRS5050	5.1	2.0-3.0	9.5	2.8	5.0	5.0	9.6	
SRS5060	5.1	3.0-4.0	9.5	2.8	6.0	5.0	9.6	
SRS5070	5.1	4.0-5.0	9.5	2.8	7.0	5.0	11.6	
SRS5080	5.1	5.0-6.0	9.5	2.8	8.0	5.0	11.6	
SRS5090	5.1	6.0-7.0	9.5	2.8	9.0	5.0	13.6	
SRS5100	5.1	7.0-8.0	9.5	2.8	10.0	5.0	13.6	
SRS5120	5.1	8.5-10.0	9.5	2.8	12.0	5.0	16.0	
SRS6060	6.1	2.5-4.0	11.0	1.5	6.0	6.0	9.4	

