



RCCN 日成SR型开口推式尼龙铆钉 Push Snap Rivets



材质:UL合格之NYLON66,防火等级94V-2,不易老化.
用途:PC板及机板之固定,取代螺丝,不需工具即可完成装配.
特点:容易固定.
用法:先将机板及被固定板钻孔,再将本产品塞入,即可使两板相线合.
板厚:以H长度小5mm为准.
开孔:建议表格孔径负公差0.5-1mm开孔.

Material : NYLON66 UL approved,
Fireproof: 94V-2 Good quality,easy
to install

单位/Unit:mm



型号 Item No.	头部 Head W	孔径 Hole dia. W1	长度 Length H	包装 Packing pcs
SR5-991	12.6	5.3	14.4	100pcs
SR8-274G	14	6.0	8.0	100pcs
SR6-85	11.6	6.0	8.3	100pcs
SR6-041	17.3	6.3	13.5	100pcs
SR6-564	15	6.3	13.0	100pcs
SR6-526	15.8	6.3	13.5	100pcs
SR6-597	17.4	6.3	18.8	100pcs
SR6-264	15.5	6.0	21.1	100pcs
SR6-595	22.2	6.3	25.4	100pcs
SR6-335	20	6.3	17.0	100pcs
SR6-682	19.8	6.6	8.9	100pcs
SR6-1153	14.8	6.6	9.7	100pcs
SR7-97	16.8	7.0	8.0	100pcs
SR7-337	18	7.0	7.0	100pcs
SR7-90	20	7.0	8.0	100pcs
SR7-189	18	7.0	11.0	100pcs
SR7-63	20.0	7.0	11.3	100pcs
SR7-84	10.9	7.0	14.0	100pcs
SR7-425	17.5	7.2	11.0	100pcs
SR7-618	15	7.0	10.0	100pcs
SR7-276G	20	7.0	8.0	100pcs
SR7-358	16.6	7.9	15.0	100pcs
SR8-636	20	8.0	9.0	100pcs
SR8-623	20	8.0	10.0	100pcs
SR8-83	20	8.0	10.2	100pcs
SR8-248	11	8.0	10.0	100pcs
SR8-118	19.6	8.0	14.4	100pcs
SR8-88	20.2	8.0	8.7	100pcs
SR8-107	13.6	8.0	9.1	100pcs
SR8-566	18	8.0	14.0	100pcs
SR8-541	20	8.0	14.0	100pcs
SR8-633	18	8.0	16.0	100pcs
SR8-649	18	8.0	15.0	100pcs
SR8-121	17.7	8.0	21.0	100pcs
SR8-351	18	8.0	12.5	100pcs
SR9-145	15	9.0	11.8	100pcs
SR9-680	18	9.0	12.0	100pcs
SR9-641	18	9.0	15.0	100pcs
SR9-611	18	9.0	28.0	100pcs
SR9-354	20	9.7	20	100pcs
SR9-686	18	9.0	22.0	100pcs
SR10-634	20	10	13	100pcs
SR10-89	18	10	15	100pcs
SR10-141	19	10	21.2	100pcs
SR10-1119	20	10	20.7	100pcs
SR12-149	25.4	12.7	22.7	100pcs