



RCCN 日成T型铜管端子 T Copper Tube Terminals

点状窥孔 Slot spy hole



型号	尺寸 DIMENSION					
Item No.	E	D φ	d φ	W	B	L
T1.5-4	4.3	4.0	2.4	8.7	7.0	19.0
T1.5-5	5.3	4.0	2.4	8.7	7.0	19.0
T1.5-6	6.4	4.0	2.4	10.0	7.0	20.0
T2.5-4	4.3	4.3	2.7	8.7	7.0	19.0
T2.5-5	5.3	4.3	2.7	8.7	7.0	19.0
T2.5-6	6.4	4.3	2.7	10.3	7.0	21.0
T2.5-8	8.3	4.3	2.7	12.0	7.0	23.0
T4-4	4.3	4.8	3.1	8.7	9.5	21.5
T4-5	5.3	4.8	3.1	8.7	9.5	21.5
T4-6	6.4	4.8	3.1	10.3	9.5	23.5
T4-8	8.3	4.8	3.1	12.5	9.5	28.5
T6-4	4.3	5.5	3.8	10.3	10.0	26.0
T6-5	5.3	5.5	3.8	10.3	10.0	26.0
T6-6	6.4	5.5	3.8	10.3	10.0	26.0
T6-8	8.3	5.5	3.8	13.9	10.0	29.0
T6-10	10.5	5.5	3.8	13.9	10.0	29.0
T10-4	4.3	6.9	4.7	11.9	11.5	27.5
T10-5	5.3	6.9	4.7	11.9	11.5	27.5
T10-6	6.4	6.9	4.7	11.9	11.5	27.5
T10-8	8.3	6.9	4.7	13.5	11.5	30.5
T10-10	10.5	6.9	4.7	15.0	11.5	30.5
T10-12	13.2	6.9	4.7	17.0	11.5	34.0
T16-5	5.3	7.8	5.6	12.0	12.0	27.5
T16-6	6.4	7.8	5.6	12.0	12.0	27.5
T16-8	8.3	7.8	5.6	13.5	12.0	31.0
T16-10	10.5	7.8	5.6	16.0	12.0	32.0
T16-12	13.2	7.8	5.6	17.0	12.0	37.5
T25-6	6.4	9.5	7.1	14.0	13.5	34.0
T25-8	8.3	9.5	7.1	14.0	13.5	34.0
T25-10	10.5	9.5	7.1	16.0	13.5	37.0
T25-12	13.2	9.5	7.1	18.0	13.5	40.0
T35-6	6.4	11.0	8.2	16.5	16.0	39.0
T35-8	8.3	11.0	8.2	16.5	16.0	39.0
T35-10	10.5	11.0	8.2	16.5	16.0	43.0
T35-12	13.2	11.0	8.2	18.0	16.0	43.0
T35-14	14.5	11.0	8.2	20.0	16.0	48.0
T35-16	16.5	11.0	8.2	23.0	16.0	48.0
T40-6	6.4	11.2	9.0	17.0	17.0	44.0

型号	尺寸 DIMENSION					
Item No.	E	D φ	d φ	W	B	L
T40-8	8.3	11.2	9.0	17.0	17.0	44.0
T40-10	10.5	11.2	9.0	17.0	17.0	44.0
T40-12	13.2	11.2	9.0	18.0	17.0	44.0
T50-6	6.4	12.5	9.5	18.0	20.0	45.0
T50-8	8.3	12.5	9.5	18.0	20.0	45.0
T50-10	10.5	12.5	9.5	18.0	20.0	49.0
T50-12	13.2	12.5	9.5	18.0	20.0	49.0
T50-14	14.5	12.5	9.5	22.0	20.0	54.0
T50-16	16.5	14.0	9.5	25.0	23.0	62.0
T50-20	21.0	14.0	9.5	30.0	23.0	68.0
T70-8	8.3	15.0	11.5	22.0	20.0	47.6
T70-10	10.5	15.0	11.5	22.0	20.0	51.6
T70-12	13.2	15.0	11.5	22.0	20.0	51.6
T70-14	14.5	15.0	11.5	22.0	20.0	62.6
T70-16	16.5	15.0	11.5	22.0	20.0	62.6
T70-20	21.0	15.0	11.5	30.0	20.0	62.6
T95-8	8.3	17.0	13.5	25.0	22.0	55.8
T95-10	10.5	17.0	13.5	25.0	22.0	55.8
T95-12	13.2	17.0	13.5	25.0	22.0	55.8
T95-14	14.5	17.0	13.5	25.0	22.0	66.8
T95-16	16.5	17.0	13.5	25.0	22.0	66.8
T95-20	21.0	17.0	13.5	28.0	22.0	66.8
T120-10	10.5	20.0	15.6	29.0	27.0	71.5
T120-12	13.2	20.0	15.6	29.0	27.0	71.5
T120-14	14.5	20.0	15.6	29.0	27.0	71.5
T120-16	16.5	20.0	15.6	29.0	27.0	71.5
T120-20	21.0	20.0	15.6	29.0	27.0	71.5
T150-10	10.5	21.0	16.5	30.6	32.0	78.0
T150-12	13.2	21.0	16.5	30.6	32.0	78.0
T150-14	14.5	21.0	16.5	30.6	32.0	78.0
T150-16	16.5	21.0	16.5	30.6	32.0	78.0
T150-20	21.0	21.0	16.5	30.6	32.0	78.0
T185-10	10.5	23.6	18.4	34.0	34.0	84.0
T185-12	13.2	23.6	18.4	34.0	34.0	84.0
T185-14	14.5	23.6	18.4	34.0	34.0	84.0
T185-16	16.5	23.6	18.4	34.0	34.0	84.0
T185-20	21.0	23.6	18.4	34.0	34.0	84.0
T240-10	10.5	26.4	21.2	38.5	37.0	90.0
T240-12	13.2	26.4	21.2	38.5	37.0	90.0
T240-14	14.5	26.4	21.2	38.5	37.0	90.0
T240-16	16.5	26.4	21.2	38.5	37.0	90.0
T240-20	21.0	26.4	21.2	38.5	37.0	90.0
T300-10	10.5	28.6	23.4	42.0	40.0	96.0
T300-12	13.2	28.6	23.4	42.0	40.0	96.0
T300-14	14.5	28.6	23.4	42.0	40.0	96.0
T300-16	16.5	28.6	23.4	42.0	40.0	96.0
T300-20	21.0	28.6	23.4	42.0	40.0	96.0
T400-10	10.5	32.8	26.8	48.0	37.0	104.7
T400-12	13.2	32.8	26.8	48.0	37.0	104.7
T400-14	14.5	32.8	26.8	48.0	37.0	104.7
T400-16	16.5	32.8	26.8	48.0	37.0	104.7
T400-20	21.0	32.8	26.8	48.0	37.0	104.7
T500-10	10.5	38.4	29.8	55.0	46.5	115.5
T500-12	13.2	38.4	29.8	55.0	46.5	115.5
T500-14	14.5	38.4	29.8	55.0	46.5	115.5
T500-16	16.5	38.4	29.8	55.0	46.5	115.5
T500-20	21.0	38.4	29.8	55.0	46.5	115.5
T630-10	10.5	44.7	34.5	64.0	50.0	133.1
T630-12	13.2	44.7	34.5	64.0	50.0	133.1
T630-14	14.5	44.7	34.5	64.0	50.0	133.1
T630-16	16.5	44.7	34.5	64.0	50.0	133.1
T630-20	21.0	44.7	34.5	64.0	50.0	133.1